

TOP 100

Rinnensystem TOP 100 Klasse C250,
inkl. Kunststoffrost und Arretierung mit verzinktem Kantenschutz

| Artikel | Baumasse mm | | kg | Stk. Pal. | Bezeichnung |
|------------|-------------|------|------|--------------|---|
| | Länge | Höhe | | | |
| 1-0.0KC | 1000 | 160 | 42.5 | 24 | Basiselement 1000mm  Mit Gefälle erhältlich |
| 1-5.0KC | 1000 | 185 | 46.6 | 24 | |
| 1-10.0KC | 1000 | 210 | 50.4 | 24 | |
| 1-0.05KC | 500 | 160 | 22.0 | 48 | Basiselement 500mm  |
| 1-5.05KC | 500 | 185 | 23.5 | 48 | |
| 1-10.05KC | 500 | 210 | 24.5 | 48 | |
| 1-0.0KCA | 1000 | 160 | 41.5 | 20 | Ablaufelement 1000mm  |
| 1-5.0KCA | 1000 | 185 | 45.6 | 20 | |
| 1-10.0KCA | 1000 | 210 | 49.4 | 20 | |
| 1-0.05KCS | 500 | 160 | 21.0 | - | Sonderelement für seitlichen Anschluss 500mm  |
| 1-5.05KCS | 500 | 185 | 22.5 | - | |
| 1-10.05KCS | 500 | 210 | 23.5 | - | |
| 1-41KC | 500 | 500 | 48.0 | 10 | Einlaufkasten 500mm  |